


Appendix A-8

Sign Lighting Tables

The attached sign lighting tables have been developed by TEDD to represent current practice in Sign Lighting. These tables are updated on a periodic basis to reflect changes in design, application, maintenance, and technology. Always check that you are using the most recent revision of these tables before proceeding with your design.



SIGN LIGHTING SCHEDULE

PANEL WIDTH (FEET)	SPACING		NUMBER LIGHTS NEEDED	PANEL HEIGHT, FEET													
	D (FEET)	C (FEET)		6	7	8	9	10	11	12	13	14	15	16	17	18	19
	LUMINAIRE WATTAGE																
8	2	4	2	250	250	250	250	250	250	250	250	250	250	250	250	400	400
9	2	5	2	250	250	250	250	250	250	250	250	250	250	250	400	400	400
10	3	4	2	250	250	250	250	250	250	250	250	250	250	250	250	400	400
11	3	5	2	250	250	250	250	250	250	250	250	250	250	250	400	400	400
12	3	6	2	250	250	250	250	250	250	250	250	250	250	400	400	400	400
13	2.5	4	3	250	250	250	250	250	250	250	250	250	250	250	250	400	400
14	2	5	3	250	250	250	250	250	250	250	250	250	250	250	400	400	400
15	2.5	5	3	250	250	250	250	250	250	250	250	250	250	250	400	400	400
16	3	5	3	250	250	250	250	250	250	250	250	250	250	250	400	400	400
17	3	5.5	3	250	250	250	250	250	250	250	250	250	250	250	400	400	400
18	3	6	3	250	250	250	250	250	250	250	250	250	250	400	400	400	400
19	2	5	4	250	250	250	250	250	250	250	250	250	250	250	400	400	400
20	2.5	5	4	250	250	250	250	250	250	250	250	250	250	250	400	400	400
21	3	5	4	250	250	250	250	250	250	250	250	250	250	250	400	400	400
22	2	6	4	250	250	250	250	250	250	250	250	250	250	400	400	400	400
23	2.5	6	4	250	250	250	250	250	250	250	250	250	250	400	400	400	400
24	3	6	4	250	250	250	250	250	250	250	250	250	250	400	400	400	400

MARYLAND STATE HIGHWAY ADMINISTRATION

Office of Traffic and Safety
 Traffic Engineering Design Division
 Traffic Control Devices Design Manual

PANEL WIDTH (FEET)	SPACING		NUMBER LIGHTS NEEDED	PANEL HEIGHT, FEET													
	D (FEET)	C (FEET)		6	7	8	9	10	11	12	13	14	15	16	17	18	19
	LUMINAIRE WATTAGE																
25	2.5	5	5	250	250	250	250	250	250	250	250	250	250	250	400	400	400
26	3	5	5	250	250	250	250	250	250	250	250	250	250	250	400	400	400
27	2.5	5.5	5	250	250	250	250	250	250	250	250	250	250	250	400	400	400
28	2	6	5	250	250	250	250	250	250	250	250	250	250	250	400	400	400
29	2.5	6	5	250	250	250	250	250	250	250	250	250	250	250	400	400	400
30	3	6	5	250	250	250	250	250	250	250	250	250	250	250	400	400	400
31	3	5	6	250	250	250	250	250	250	250	250	250	250	400	400	400	400
32	3.5	5	6	250	250	250	250	250	250	250	250	250	250	400	400	400	400
33	1.5	6	6	250	250	250	250	250	250	250	250	250	250	400	400	400	400
34	2	6	6	250	250	250	250	250	250	250	250	250	250	400	400	400	400
35	2.5	6	6	250	250	250	250	250	250	250	250	250	250	400	400	400	400
36	3	6	6	250	250	250	250	250	250	250	250	250	250	400	400	400	400
37	2	5.5	7	250	250	250	250	250	250	250	250	250	250	250	400	400	400
38	2.5	5.5	7	250	250	250	250	250	250	250	250	250	250	250	400	400	400
39	3	5.5	7	250	250	250	250	250	250	250	250	250	250	250	400	400	400
40	2	6	7	250	250	250	250	250	250	250	250	250	250	400	400	400	400
41	2.5	6	7	250	250	250	250	250	250	250	250	250	250	400	400	400	400
42	3	6	7	250	250	250	250	250	250	250	250	250	250	400	400	400	400
43	3.5	6	7	250	250	250	250	250	250	250	250	250	250	400	400	400	400
44	2.75	5.5	8	250	250	250	250	250	250	250	250	250	250	250	400	400	400

PANEL WIDTH (FEET)	SPACING		NUMBER LIGHTS NEEDED	PANEL HEIGHT, FEET														
	D (FEET)	C (FEET)		6	7	8	9	10	11	12	13	14	15	16	17	18	19	
	LUMINAIRE WATTAGE																	
45	1.5	6	8	250	250	250	250	250	250	250	250	250	250	250	400	400	400	400
46	2	6	8	250	250	250	250	250	250	250	250	250	250	250	400	400	400	400
47	2.5	6	8	250	250	250	250	250	250	250	250	250	250	250	400	400	400	400
48	3	6	8	250	250	250	250	250	250	250	250	250	250	250	400	400	400	400